

EC Declaration of Conformity

PULS

PULS as the manufacturer declares hereby, that all products listed below, are in conformity with the provisions of the following European Directives:

2004/108/EC Electromagnetic Compatibility Directive
2006/95/EC Low Voltage Directive

Model		Output	Input
SLR01	Redundancy Module	40A	40A
SLR02	Redundancy Module	30A	2x 30A/2x 15A
YRM2.DIODE	Redundancy Module	20A	2x 12.5A/2x 10A
YRM.DIODE	Decoupling Module	20A	2x 12.5A/2x 10A
MLY02.100	Decoupling Module	10A	2x 10A/2x 5A

The following standards were used to assess the products:

EN 61000-6-3:2007 Generic emission standard for residential environments

(also meets the requirements of EN 61000-6-4:2001 for industrial environments)

- EN 55011:1998 + A1:1999 + A2:2002 class B and EN 55022:2006 class B radio disturbance
Configuration: Power supply on table, resistance load,
line length load/mains line: 1m for line-routed interference (150kHz-30MHz)
line length load/mains line: 1m horizontal and 0,8m vertical for radiated interference (30MHz-1GHz)

EN 61000-6-2:2005 Generic immunity standard for industrial environments

(also meets the requirements of EN 61000-6-1:2001 for residential environments)

- IEC 61000-4-2 / EN 61000-4-2:1995 + A1:1998 + A2:2001 Electrostatic discharge test
- IEC 61000-4-3 / EN 61000-4-3:2003 Radiated, radio-frequency, electromagnetic field
- IEC 61000-4-4 / EN 61000-4-4 :2004 Electrical fast transient/ burst immunity test
- IEC 61000-4-6 / EN 61000-4-6:1996 + A1:2001 Conducted disturbances, radio-frequency fields

EN 60950-1:2006

Information technology equipment - Safety – Part 1: General requirements

(also meets the requirements of EN 60950-1:2001)

PULS GmbH
Arabellastraße 15
81925 Muenchen
Germany

Muenchen, 2007-12-11

This is the internet version of the EC Declaration of Conformity which bears no signature but is identical to the signed document. If a copy of a declaration with an actual signature should be needed, please contact your local PULS sales office.

Bernhard Erdl, Managing Director

No. G RED 1