



SSB7020 SERIES – Low Profile SMD Power Inductors




RoHS Compliant

PART NUMBERING SYSTEM

SSB	7020	—	100M	—	LF
TYPE	DIMENSIONS		INDUCTANCE		LEAD FREE

SHAPES AND DIMENSIONS


UNIT : mm



A=10.18Max. B= 7.2±0.3 C=7.2±0.3 D=2.00 Max

RECOMMENDED PATTERNS

UNIT : mm



G=3.50 H=3.00 I=2.25




SSB7020 SERIES – Low Profile SMD Power Inductors

SPECIFICATION TABLE

PART NUMBER	INDUCTANCE (μ H)	DCR (m Ω) (Max.)	Isat (A)	Irms (A)	TEST FREQ. (f)
SSB7020-2R2N-LF	2.2 \pm 30%	51	4.60	3.00	100KHz/0.1V
SSB7020-3R3N-LF	3.3 \pm 30%	70	4.00	2.20	100KHz/0.1V
SSB7020-4R7N-LF	4.7 \pm 30%	96	3.50	2.00	100KHz/0.1V
SSB7020-6R8N-LF	6.8 \pm 30%	120	2.70	1.75	100KHz/0.1V
SSB7020-100M-LF	10.0 \pm 20%	186	2.00	1.40	100KHz/0.1V
SSB7020-150M-LF	15.0 \pm 20%	255	1.50	1.10	100KHz/0.1V
SSB7020-220M-LF	22.0 \pm 20%	306	1.30	1.07	100KHz/0.1V
SSB7020-330M-LF	33.0 \pm 20%	501	1.20	0.85	100KHz/0.1V
SSB7020-470M-LF	47.0 \pm 20%	693	1.00	0.75	100KHz/0.1V

- ※ Inductance measured using a Coilmaster SMD fixture in an Agilent/HP 4284A or equivalent.
- ※ Isat: DC current at which the inductance drops 10% (typ) from its value without current.
- ※ Irms: Average current for 30°C (max) rise from +25°C ambient.
- ※ Operating temperature range : -40°C to + 125 °C.

PACKAGING SPECIFICATION



SERIES	STAYLE	Q' TY (PCS)	DIMENSIONS (m/m)								
			A	B \pm 0.8	C \pm 0.5	D	G ⁺	N ⁰	P	Po	T
SSB7020	13-16	2000	330	21	13	16	18	50	8	4	22.4