

EI series 1207 - 2.3VA h21.7

- Safety transformers according to the European standard CEI EN 61558-1 and CEI EN 61558-2-6
- Primary and Secondary two chamber windings
- Epoxy encapsulated
- Marking on primary side
- Tin-plated phosphor bronze pins
- Pins size: $\varnothing 0,9$ mm typ , length 4mm min
- Only electrically used pins are mounted
- 5000V dielectric strength between primary and secondary windings
- 100% tested
- Custom versions on request



2.3 VA - t_a70/B (2.5 VA - t_a40/B)

Code	Primary (50-60Hz)	Secondary ¹ (t_a70°)	Secondary ¹ (t_a40°)	Layout	Overload Protection
1207S106	230V	6V - 383 mA	(6V - 416 mA)	Drawing 1	inherently short-circuit proof
1207S109	230V	9V - 256 mA	(9V - 277 mA)	Drawing 1	inherently short-circuit proof
1207S112	230V	12V - 192 mA	(12V - 208 mA)	Drawing 1	inherently short-circuit proof
1207S115	230V	15V - 153 mA	(15V - 166 mA)	Drawing 1	inherently short-circuit proof
1207S118	230V	18V - 128 mA	(18V - 138 mA)	Drawing 1	inherently short-circuit proof
1207S124	230V	24V - 96 mA	(24V - 104 mA)	Drawing 1	inherently short-circuit proof
1207S206	230V	2x 6V - 192 mA	(2x 6V - 208 mA)	Drawing 2	inherently short-circuit proof
1207S209	230V	2x 9V - 128 mA	(2x 9V - 138 mA)	Drawing 2	inherently short-circuit proof
1207S212	230V	2x 12V - 96 mA	(2x 12V - 104 mA)	Drawing 2	inherently short-circuit proof
1207S215	230V	2x 15V - 77 mA	(2x 15V - 83 mA)	Drawing 2	inherently short-circuit proof
1207T106	115V	6V - 383 mA	(6V - 416 mA)	Drawing 1	inherently short-circuit proof
1207T109	115V	9V - 256 mA	(9V - 277 mA)	Drawing 1	inherently short-circuit proof
1207T112	115V	12V - 192 mA	(12V - 208 mA)	Drawing 1	inherently short-circuit proof
1207T115	115V	15V - 153 mA	(15V - 166 mA)	Drawing 1	inherently short-circuit proof
1207T118	115V	18V - 128 mA	(18V - 138 mA)	Drawing 1	inherently short-circuit proof
1207T124	115V	24V - 96 mA	(24V - 104 mA)	Drawing 1	inherently short-circuit proof
1207T206	115V	2x 6V - 192 mA	(2x 6V - 208 mA)	Drawing 2	inherently short-circuit proof
1207T209	115V	2x 9V - 128 mA	(2x 9V - 138 mA)	Drawing 2	inherently short-circuit proof
1207T212	115V	2x 12V - 96 mA	(2x 12V - 104 mA)	Drawing 2	inherently short-circuit proof
1207T215	115V	2x 15V - 77 mA	(2x 15V - 83 mA)	Drawing 2	inherently short-circuit proof

Dimensions	mm	Drawing 1 (bottom view)	Drawing 2 (bottom view)	Dimensions	.stp file Download
a max	41,4				
b max	34,9				
h max	21,7				
x typ	5,0				
y typ	25,0				

¹ Rated voltage (No load voltage x 1,52).