

## UI series U3016 - 10VA

- Safety transformers according to the European standard CEI EN 61558-1 and CEI EN 61558-2-6
- Primary and Secondary two chamber windings
- Epoxy encapsulated
- Marking on primary side
- Tin-plated phosphor bronze pins
- Pins size:  $\varnothing 0,9$  mm typ , length 4mm min
- Only electrically used pins are mounted
- 5000V dielectric strength between primary and secondary windings
- 100% tested
- Custom versions on request
- Fixing with 4 self-tapping screws 3x12mm



## 10 VA - $t_a50/B$



Code	Primary (50-60Hz)	Secondary <sup>1</sup>	Output fuses <sup>2</sup>
U3016S06	2x115V	2x 6V - 833 mA	2 fuses 1000 mA
U3016S09	2x115V	2x 9V - 555 mA	2 fuses 630 mA
U3016S12	2x115V	2x 12V - 416 mA	2 fuses 500 mA
U3016S15	2x115V	2x 15V - 333 mA	2 fuses 400 mA
U3016S18	2x115V	2x 18V - 278 mA	2 fuses 315 mA

Dimensions	mm	Layout (bottom view)	Dimensions	.stp file Download
a max	53,7			
b max	44,4			
h max	28,4			
x typ	5,0			
y typ	35,0			
c typ	47,7			
d typ	37,7			

230V / 2xVsec	230V / 2xIsec	115V / 2xVsec	115V / 2xIsec
Primary double voltage Secondary double voltage	Primary double voltage Secondary double current	Primary double current Secondary double voltage	Primary double current Secondary double current

<sup>1</sup> Rated voltage (No load voltage x 1,35).

<sup>2</sup> See the output fuses notes on back cover. Different overload protection are possible if the user performs proper tests to assure the relevant standard compliance.