

B向











Material :

ⓐ Housing : PA66(UL94V-0)
ⓑ Contact : Phosphor Bronze
ⓒ Cage : Brass , Ni Plated
ⓓ Screws : Steel , Cr^{3+}Zn Plated
ⓔ Cover : PA66(UL94V-0)

Electrical :

	UL	IEC
1.Rated Voltage :	300V	250V
2.Rated Current :	8A	7A
3.Torque Value :	M2 , 1.77Lb.in	M2 , 0.2N.m
4.Wire Range:	28-16AWG	0.5-1.5mm^2

5.Stripping Length : 6-7mm
6.Withstanding Voltage : AC1600V/1Min.
7.Operating Temperature : -40°C~+105°C
8.RoHS Compliance
9.Safty Approval :
10.Undimensioned Tolerances:

Pitch Range In mm			Nominal Dimension Range In mm					— ⌒ ⌓
≤6	6 ~ 10	10 ~ 24	≤30	30 ~ 60	60 ~ 100	100 ~ 150	>150	0.05/10 ∠
±0.10	±0.15	±0.25	±0.20	±0.30	±0.50	±0.70	±1.00	±0.1°

15EGTK - 3.5 - XXP - X X - 00 AH
① ② ③ ④ ⑤ ⑥ ⑦

① Sereies No.

② Pitch

③ Poles
02 02Contacts
03 03Contacts
...
24 24Contacts

④ 1 Single Pitch
2 Double Pitch

⑤ Color: 1 Grey
2 Blue
3 Black
4 Green(Standard For AH)
5 Orange
6 Red
7 Transparent
8 Yellow
9 White

⑥ Customer Request : 00--Standard

⑦ AH--Standard(PA66)

ALTERNATIVES BY BEC DISTRIBUTION LTD

DETACHED LISTS

APPD:	MA_8/13/16 '	PART NO.	BC15EGTK-3.5-XXP-XX-00AH
CHKD:	Yu_8/12/16 '		
DRFT:	Chen_8/11/16 '	DRAWING NO.	REV 1
			SHEET 1/1
THIRD ANGLE PROJECTION		MM (INCH) DO NOT SCALE DRAWING	SCALE 1/1

8 7 6 5 4 3 2 1
H G F E D C B A